

Industrial Single Board Computer

Mini-ITX motherboard

LV-67L

Intel® Sandy Bridge Processor 807UE/847E with DDRIII SO-DIMM, CRT, DVI, LVDS, Gigabit LAN, USB2.0 ,PCIE x16, PCI Express mini card, mSATA, Serial ATAll, Serial ATAIll, HD Audio, SPDIF



Form Factor	Mini-ITX motherboard
CPU	Intel® Celeron® Processor 807UE 1.0GHz (LV-67LNB) Intel® Celeron® Processor 847E 1.1GHz (LV-67LBU) Package type : FCBGA1023
Memory	1 x DDRIII SO-DIMM 1066/1333 MHz up to 4GB (LV-67LNB) 2 x DDRIII SO-DIMM 1066/1333 MHz up to 16GB (LV-67LBU) Support Non-ECC, unbuffered memory only
Chipset	Intel HM65
Real Time Clock	Chipset integrated RTC with onboard lithium battery
Watchdog Timer	Generates a system reset with internal timer for 1min/s ~ 255min/s
Power Management	Supports ACPI 3.0 compliant
Serial ATA Interface	4 x serial ATAll interface with 300MB/s transfer rate 2 x serial ATAIll interface with 600MB/s transfer rate The HM65 doesn't support RAID function.
Integrated Graphics	Intel® integrated extreme HD graphics Technology
VGA Interface	Onboard DSUB15 connector for VGA interface
LVDS Interface	Onboard 24-bit dual channel LVDS connector with +3.3V/+5V/+12V supply
DVI interface	Onboard DVI with 20-pin connector
Audio Interface	Realtek ALC888 HD Audio
LAN Interface	1 x Intel 82579LM Gigabit LAN 1 x Intel 82574L Gigabit LAN
GPIO Interface	Onboard programmable 8-bit Digital I/O interface
Extended Interface	LV-67LNB support 2 x PCIE mini card socket, 1 x SIM socket. LV-67LBU support 1 x PCIE x16 slot, 2 x PCIE mini card socket, 1 x SIM socket. Optional support mSATA(SATAII) for above models in Mini_Card2,but SATA6 will be disabled.
Internal I/O Port	3 x RS232,1 x SMBUS, 1 x GPIO, 6 x USB2.0 ports, 1 x IrDA, 1 x DVI , 1 x LVDS, 4 x Serial ATAll, 2 x Serial ATAIll, 1 x Front panel Audio and 1 x CDIN
External I/O Port	1 x PS/2, 2 x LAN ports, 1 x VGA port, 4 x USB2.0 ports, 1 x RS232/422/485, 2 x RS232, 1 x SPDIF and 1 x 2 Channel HD Audio
Power Requirement	Standard 24-pin ATX power supply or 9~24V full range DC Input
Dimension	170mm x 170mm
Temperature	Operating within 0~60 centigrade Storage within -20~85 centigrade

Ordering Code

LV-67LNB	Intel® Celeron® Processor 807UE + HM65 with Onboard VGA, LVDS, DVI, LAN, USB2.0, HD Audio, SATAII ,SATAIII, SMBUS, LPC, SIM, GPIO and PCI Express mini card.
LV-67LNBS	Intel® Celeron® Processor 807UE + HM65 with Onboard VGA, LVDS, DVI, LAN, USB2.0, HD Audio, SATAII ,SATAIII, SMBUS, LPC, SIM, GPIO, PCI Express mini card and mSATA.
LV-67LBU	Intel® Celeron® Processor 847E + HM65 with Onboard VGA, LVDS, DVI, LAN, USB2.0, HD Audio, SATAII ,SATAIII, SMBUS, LPC, SIM, GPIO, PCIE x16 and PCI Express mini card.
LV-67LBUS	Intel® Celeron® Processor 847E + HM65 with Onboard VGA, LVDS, DVI, LAN, USB2.0, HD Audio, SATAII ,SATAIII, SMBUS, LPC, SIM, GPIO, PCIE x16 , PCI Express mini card and mSATA.

Taiwan Commate Computer Inc.

19F, NO. 94, Sec. 1, Shin Tai Wu Rd., Hsi Chih, Taipei Shien, Taiwan.

TEL: +886-2-26963909

Website:www.commell.com.tw

FAX: +886-2-26963911

E-mail:info@commell.com.tw



Stage For Your Success