

### M2-350

### Features

- Low power consumption and high performance
- PCIe to Dual / Quad Gigabit LAN
- M.2 Key M 2280 interface



#### M2-3502

##### Product Description

Host Interface	M.2 KEY M
Controller	Intel® I350-AM2
Dimension	22.00mm x 80.00mm

#### M2-3504

##### Product Description

Host Interface	M.2 KEY M
Controller	Intel® I350-AM4
Dimension	22.00mm x 80.00mm

#### Operating Conditions

Voltage	3.3V +/-5%
Temperature	0~55°C with airflow (Note)
Storage Temperature	-40~+85°C

#### General Specifications

Compliance	IEEE 802.3 Ethernet interface for 1000Base-T, 100Base-TX, and 10Base-T applications (802.3, 802.3u, 802.3ab).
Transfer Rate	1000 Mb/s, 100 Mb/s, or 10 Mb/s
Support OS	Win7 x32&x64, Win8 x32&x64, Win8.1 x32&x64, Win10 x32&x64, Win server 2012 R2. Linux (kernel versions 2.6.30 or newer)

#### Ordering Code

M2-3502	M.2 card support dual Gigabit Ethernet (Incl. connection cables and dual RJ45 adapter)
M2-3504	M.2 card support quad Gigabit Ethernet (Incl. connection cables and 2 x dual RJ45 adapter)

**Note:** Airflow required for operation when the integrated system is used together.